

Stainless steel tanks



Free standing or wall mounted

MODEL VT100C / VT180C		
H x D x W VT100C	mm	1140x575x540
H x D x W VT180C	mm	1540x575x540
Voltage / frequency	Volt / Hz	220-240 / 50
Heat pump output	kW	0,897
Heat pump input (13A)	kW	0,340
Heating element	kW	1,5 / 2,0
Water temperature	°C	5 - 62
Working air temperature	°C	+5 / +35
Quantity of air	m3/h	100 / 200
Tank Capacity VT100C	L	100
Tank Capacity VT180C	L	180
Stainless steel tank		Standard
Working pressure max	Bar	10
Energy class		A+

QUALITY

Quality is of highest priority for all Vesttherm product. Only top quality and approved components are used in our products.

ENVIRONMENT

On various models we are now ready to offer products with the natural refrigerant propane (R290) which is 100% HFC free and therefore totally harmless towards the environment.

EFFICIENCY

Vesttherm products have very high insulation rates which gives a very low heat loss. Our COP values are among the highest on the market.

ABOUT Vesttherm

High quality hot water heat pumps

Vesttherm is a Danish owned manufacturer of hot water heat pumps. For more than 30 years we have produced high quality products throughout Europe.

We are known for our high quality, our high flexibility and our ability to produce customized solutions.

Vesttherm's product range includes many different consumer solutions tailored to our customers needs.



Vesttherm A/S
Øresundsvej 10
DK-6715 Esbjerg N
Denmark
Phone +45 75 14 02 44
Fax +45 75 14 48 18
mail: vesttherm@vesttherm.dk

WWW.VESTTHERM.DK

VESTTHERM IS SPECIALIZED IN
PRIVATE LABEL & OEM BUSINESS

Vesttherm

High quality hot water heat pumps

HIGH QUALITY
HIGH EFFICIENCY
HIGH FLEXIBILITY
UNIQUE DESIGNS



ALL PRODUCTS ARE PRODUCED
& DESIGNED IN DENMARK



MODEL VT 3130		
H x D	mm	1768 x Ø707
Voltage / frequency	Volt / Hz	220-240 / 50
Heat pump output	kW	1,42
Heat pump input (13A)	kW	0,395
Heating element	kW	1,5 / 2,0
Water temperature	°C	5 - 62
Working air temperature	°C	-10 / +35
Quantity of air	m3/h	200 / 300
Tank Capacity VT3130	L	270
Tank Capacity VT3131	L	258
Tank Capacity VT3132	L	242
Enameled Tank	Optional:	Stainless Steel
Working pressure max	Bar	10
Energy class		A+

MODEL VT 3130 ECO		
H x D	mm	1916 x Ø707
Voltage / frequency	Volt / Hz	220-240 / 50
Heat pump output	kW	1,70
Heat pump input (13A)	kW	0,60
Heating element	kW	1,5 / 2,0
Water temperature	°C	5 - 62
Working air temperature	°C	-10 / +35
Quantity of air	m3/h	200 / 300
Tank Capacity VT3130 ECO	L	270
Tank Capacity VT3131 ECO	L	258
Tank Capacity VT3132 ECO	L	242
Enameled Tank	Optional:	Stainless Steel
Working pressure max	Bar	10
Energy class		A+

MODEL VT 3150 ECO		
H x D	mm	1768 x Ø707
Voltage / frequency	Volt / Hz	220-240 / 50
Heat pump output	kW	1,98
Heat pump input (13A)	kW	0,490
Heating element	kW	1,5 / 2,0
Water temperature	°C	5 - 62
Working air temperature	°C	-10 / +35
Quantity of air	m3/h	200 / 300
Tank Capacity VT3150	L	310
Enameled Tank	Optional:	Front Flange
Working pressure max	Bar	10
Energy class		A+

MODEL VT 3160		
H x D	mm	1916 x Ø707
Voltage / frequency	Volt / Hz	220-240 / 50
Heat pump output	kW	2,389
Heat pump input (13A)	kW	0,724
Heating element	kW	1,5 / 2,0
Water temperature	°C	5 - 62
Working air temperature	°C	-10 / +35
Quantity of air	m3/h	200 / 300
Tank Capacity VT3160	L	395
Front flange		standard
Enameled Tank		
Working pressure max	Bar	10
Energy class		A+

MODEL VT 2130		
H x W x D	mm	1750x600x720
Voltage / frequency	Volt / Hz	220-240 / 50
Heat pump output	kW	2,15
Heat pump input (13A)	kW	0,50
Heating element	kW	1,5 / 2,0
Water temperature	°C	5 - 62
Working air temperature:	°C	-10 / +35
Quantity of air	m3/h	200 / 300
Tank Capacity VT2130	L	270
Tank Capacity VT2131	L	258
Tank Capacity VT2132	L	242
Enameled Tank	Optional:	Stainless Steel
Working pressure max	Bar	10
Energy class		A

MODEL VT 2130 ECO		
H x D	mm	1887x595x721
Voltage / frequency	Volt / Hz	220-240 / 50
Heat pump output	kW	1,70
Heat pump input (13A)	kW	0,60
Heating element	kW	1,5 / 2,0
Water temperature	°C	5 - 62
Working air temperature	°C	-10 / +35
Quantity of air	m3/h	200 / 300
Tank Capacity VT2130 ECO	L	270
Tank Capacity VT2131 ECO	L	258
Tank Capacity VT2132 ECO	L	242
Enameled Tank	Optional:	Stainless Steel
Working pressure max	Bar	10
Energy class		A+